
SUPER 30 AUTO EJECT - AE 30 AMP AIR-ELECTRIC AUTO EJECT

Features

- 30A, 120V, 175PSI
- Heavy duty pin and sleeve contacts provide reliable connection over years of insertion/eject cycles
- Air connection made through a brass fitting containing a shut-off valve
 - Shut-off valve opens when plug is inserted to supply air pressure to the vehicle
 - Shut-off valve closes automatically when plug is ejected sealing off the air supply air
- Upon sensing engine start, the plug ejects from receptacle and away from vehicle path; eliminating dangerous severing of cord
- Air-Electric energizing is delayed until detector pin senses plug is inserted, eliminating terminal arcing
- After eject, weatherproof cover snaps into position
 over inlet
- Smooth sculpted cover, no sharp edges
- Weatherproof back enclosure with watertight cable fittings protects mechanism from road contamination
- System includes: Air-Electric Eject, Cover, Plug, and 30' of Air Line
- 2 Year Warranty





Red

BL

Blue

Weatherproof



Black



30A, 120V, 175PSI Plug



Specifications:

Input Voltage (Volts DC): 10 - 28 Input Current (Amps): 1.6 max Output Voltage (Volts AC): 120 Output Current (Amps): 30 Output Air Rating (PSI): 175 Output Fuse (Supplied with unit): 2 Amps Weight (Ibs.): 8 Warranty: 2 Years



| Part Number | Description | Electrical Data | | | | | Dimensions | | | Wqt. |
|----------------|----------------------------------|-----------------|---------|----------|---------|-------------|------------|-------|-------|-------|
| | | DC Volts | DC Amps | AC Volts | AC Amps | Maximum PSI | Н | W | D | vvgı. |
| 091-169-30-120 | Super 30 Air-Electric Auto Eject | 12 / 24 | 1.6 | 120 | 30 | 175 | 8.90" | 6.68" | 6.20" | 8 |



800-346-0857

sales@kussmaul.com | www.kussmaul.com

170 Cherry Avenue, West Sayville, New York 11796